


CATALOG C-BLZM-1009

NIBCO®

AHEAD OF THE FLOW®



CPVC BlazeMaster®
Fire Protection Fittings

Business-to-Business Solutions

Look to NIBCO for technology leadership.

The velocity with which e-business evolves demands that new products and services be continuously developed and introduced to keep our customers at the center of our business efforts. NIBCO provides an entire suite of business-to-business solutions that is changing the way we interact with customers.



NIBCOpartner.comSM is an exclusive set of secure web applications that allow quick access to customer-specific information and online order processing. This self-service approach gives you 24/7 access to your order status putting you in total control of your business.

Real time information includes:

- Online order entry
- Viewable invoices & reports
- Inventory availability
- Current price checks
- Order status
- Online library of price sheets, catalogs & submittals



Electronic Data Interchange (EDI) makes it possible to trade business documents at the speed of light. This technology cuts the cost of each transaction by eliminating the manual labor and paperwork involved in traditional order taking. This amounts to cost-savings, increased accuracy and better use of resources.

With EDI, you can trade:

- Purchase orders
- PO Acknowledgements
- Invoices
- Product activity data
- Advanced ship notices
- Remittance advice



Vendor Managed Inventory (VMI), a sophisticated service for automated inventory management, reduces your overhead by transferring inventory management, order entry and forecasting to NIBCO. This is an on-going, interactive partnership with NIBCO.

Through automation, VMI brings results:

- Improves customer service
- Optimum inventory efficiencies
- Better forecasting
- Cuts transaction costs
- Peace of mind
- Relief from day-to-day management





Visit our website for the most current information .

Table Of Contents

Numerical Index	4
Key to NIBCO Figure Numbers.....	5
Specifications and Engineering Data.....	6
CPVC Standard Fire Protection Fittings	7-13
CPVC Threaded Fire Protection Fittings.....	14-19
Cement and Accessories.....	20-21
Typical Residential Riser	22
Valves for Residential Fire Protection.....	23
Hangers for Residential Fire Protection.....	24
Do's and Don'ts	25
CPVC Cross Reference Sheet.....	26-27
Warranty.....	30

BlazeMaster®

Numerical Index

CPVC BlazeMaster® Fire Protection Fittings

CPVC FIG NO	PAGE
5001-G	8
5001	9
5001-R	9
5003-BI	15
5003-2-BI	15
5003-S-BI	15
5003-2-S-BI	16
5004-BI	16
5006	10
5007	10
5007-R	10
5007-3-S-BI	17
5011	12
5011-R	12
5011-3-3-S-BI-L	18
5011-3-3-S-BI-S	18
5012-S-BI	18
5012-R-S-BI	18
5014-R-S-BI	18
5017	9
5018	8
5019-H	11

CPVC FIG NO	PAGE
5051-A	11
5051-H	11
5051-2A	11
5033-E	13
5035	9
5035-R	9
5035-3-S-BI-L	17
5035-3-S-BI-S	17
450-005	19
TCBR-3	19
5097-Q	20
5097-P	20
5098-Q	20
5098-P	20
5098-G	20
5096	20
5097	20
5093-S	20
5093-L	20
5094	21
5099	21

BlazeMaster®

Key to NIBCO Figure Numbers

TYPE OF MATERIAL

50 = CPVC Fire Protection

TYPE OF FITTING & DESCRIPTION

01 = Coupling
03 = Female Adapter
04 = Male Adapter
06 = 45° Elbow
07 = 90° Elbow
11 = Tee
12 = Sprinkler Head Tee (Thread on Outlet)
14 = Sprinkler Head Tee (Thread on Run)
17 = Cap
18 = Bushing
19 = Blind Flange
33 = Unions
35 = Cross
51 = Solid Flange

TYPE OF CONNECTIONS

2 = Fitting Connection Spigot
3 = Female NPT Thread Connection
4 = Male NPT Thread Connection
S = Sprinkler Head Adapter
BI = Brass Insert
R = Reducing

Fitting Terms and Abbreviations

FNPT = Female NPT Thread
MNPT = Male NPT Thread
S or SLIP = Female Socket
SPG = Male End (Spigot)
G = Grooved
L = Large
S = Small
H = Heavy
A = Van Stone 2-piece flange
Q = Quart
P = Pint

BlazeMaster®

Specifications and Engineering Data

Introduction

NIBCO® **BlazeMaster**® CPVC Fire Sprinkler products produced by NIBCO are manufactured from high quality, Post-Chlorinated Polyvinyl Chloride (CPVC), a specialty thermoplastic material tested and listed by certifying agencies for use in CPVC fire sprinkler systems. NIBCO CPVC Fire Sprinkler products provide unique advantages over traditional metal fire sprinkler systems through superior hydraulics, ease of installation and handling and quick assembly using readily available, inexpensive tools. These products also are based on a technology with a continuous and proven service history of more than forty (40) years.

Pressure Rating

NIBCO **BlazeMaster**® CPVC Fittings of nominal sizes 3/4" – 3" (20 – 80 mm) are rated for continuous service of 175 psi (1270 kPa) at 150°F (65°C).

Approvals

NIBCO **BlazeMaster**® CPVC fittings for fire sprinkler systems meet the approval and listing requirements of NFPA 13, 13D, and 13R.

NIBCO **BlazeMaster**® CPVC Fittings are listed by NSF to ANSI / NSF Standard 61 for health effects and may be used in potable water applications.

NIBCO **BlazeMaster**® CPVC Fittings carry the markings of Factory Mutual (FM) and Underwriters Laboratories Inc. (C-UL-US) for listings in the United States and Canada.

NIBCO **BlazeMaster**® CPVC 3/4" to 3" Fittings are listed by the Loss Prevention Safety Board (LPCB).

NIBCO **BlazeMaster**® CPVC Fittings are accepted for use by the City of New York Department of Buildings MEA 280-07-E.

Use with other Manufacturers' Pipes, Fittings, & Solvent Cements

NIBCO **BlazeMaster**® CPVC Fire Sprinkler products are listed by UL standard 1821 & C-UL standard UCC/ORD-C199P and FM standard 1635. These listings require rigorous testing to ensure the products will function as a component of the assembled fire protections system. For Fire Protection CPVC pipe the current UL standard is 1821 & C-UL standard UCC/ORD-C199P and FM standard 1635. NIBCO warrants our fittings with all CPVC pipe and fittings that are in compliance with the same listings by UL & FM. A current list of compatible UL and C-UL Listed CPVC manufacturers are: Viking (pipe), Harvel (pipe), TYCO Fire Products (pipe & fittings), IPEX (pipe & fittings), Victaulic (pipe) and Spears (fittings).

NOTICE: While NIBCO **BlazeMaster**® CPVC Fire Sprinkler Products are UL Listed for use in combination with other listed manufacturers' products, specific application approvals may not be the same among manufacturers. It is the installer's responsibility to verify suitability of products used in combination according to each manufacturer's installation instructions. Contact NIBCO if you have questions on any application not addressed in this manual.

Engineering Data – Product Specifications

NIBCO **BlazeMaster**® CPVC Fire Sprinkler Products are made for use with Listed CPVC Fire Sprinkler Pipe Produced in SDR 13.5 dimensions, as specified in ASTM F 442.

NIBCO **BlazeMaster**® CPVC Fire Sprinkler Fittings are produced in Schedule 40 dimensions for sizes 3/4 inch (20 mm) through 1-1/4 inch (32 mm) in accordance with ASTM F 438 and Schedule 80 dimensions for sizes 1-1/2 inch (40 mm) through 3 inch (80 mm) in accordance with ASTM F 439. These products are UL and C-UL Listed, and FM Approved for a rated working pressure of 175 psi (1200 kPa) at 150°F (65°C) for sprinkler service.

Installation Instructions

For complete installation instructions see NIBCO's "Installation and Design Manual," or for our abbreviated installer specific version, see NIBCO's "Pocket Guide".



BlazeMaster®

CPVC Standard Fire Protection Fittings


Adapters	8
Bushings	8
Caps	9
Couplings	9
Crosses	9
Elbows	10
Flanges	11
Tees	12
Unions.....	13

BlazeMaster®

BlazeMaster® Fire Protection Fittings – STANDARD

ADAPTERS

5001-G



Grooved Coupling Adapters (G x S)

UNIV. FIG. NO.	NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES	DIM. B INCHES	DIM. C INCHES	JOINT
5001-G	1-1/4"	0.17	0.83	1.04	2.98	GXS
5001-G	1-1/2"	0.20	0.95	1.17	3.15	GXS
5001-G	2"	0.30	1.18	1.43	3.37	GXS
5001-G	2-1/2"	0.52	1.43	1.74	3.66	GXS
5001-G	3"	0.72	3.50	—	—	GXS

BUSHINGS

5018



Bushing


UNIV. FIG. NO.	NOM. SIZE	APPROX. NET WT./LBS.	DIM. L INCHES	DIM. N INCHES	JOINT
5018	1"x3/4"	0.04	1.28	0.29	SPGXS
5018	1-1/4"x1"	0.08	1.41	0.29	SPGXS
5018	1-1/4"x3/4"	0.10	1.41	0.41	SPGXS
5018	1-1/2"x1-1/4"	0.07	1.54	0.27	SPGXS
5018	1-1/2"x1"	0.12	1.54	0.39	SPGXS
5018	1-1/2"x3/4"	0.16	1.54	0.53	SPGXS
5018	2"x1-1/2"	0.16	1.66	0.27	SPGXS
5018	2"x1-1/4"	0.20	1.66	0.40	SPGXS
5018	2"x1"	0.22	1.66	0.52	SPGXS
5018	2"x3/4"	0.22	1.66	0.64	SPGXS
5018	2-1/2"x2"	0.24	1.94	0.44	SPGXS
5018	2-1/2"x1-1/2"	0.36	1.94	0.57	SPGXS
5018	2-1/2"x1-1/4"	0.37	1.94	0.68	SPGXS
5018	3"x2-1/2"	0.47	2.42	0.60	SPGXS
5018	3"x2"	0.66	2.42	0.93	SPGXS

BlazeMaster®

BlazeMaster® Fire Protection Fittings – STANDARD

CAPS

5017




Caps

UNIV. FIG. NO.	NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES	STYLE	JOINT
5017	3/4"	0.04	0.31	D	S
5017	1"	0.06	0.39	D	S
5017	1-1/4"	0.22	0.41	F	S
5017	1-1/2"	0.30	0.42	F	S
5017	2"	0.42	0.44	F	S
5017	2-1/2"	0.62	1.20	D	S
5017	3"	0.96	1.26	D	S

COUPLINGS

5001

5001-R




Coupling

UNIV. FIG. NO.	NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES	JOINT
5001	3/4"	0.06	0.12	SXS
5001	1"	0.08	0.09	SXS
5001	1-1/4"	0.12	0.08	SXS
5001	1-1/2"	0.30	0.27	SXS
5001	2"	0.44	0.28	SXS
5001	2-1/2"	0.72	0.20	SXS
5001	3"	1.10	0.22	SXS
5001-R	1"x3/4"	0.08	0.29	SXS
5001-R	1-1/4"x1"	0.12	0.35	SXS
5001-R	1-1/2"x1-1/4"	0.38	0.51	SXS
5001-R	1-1/2"x1"	0.36	0.67	SXS
5001-R	1-1/2"x3/4"	0.34	0.80	SXS
5001-R	2"x1-1/2"	0.52	0.51	SXS
5001-R	2"x1"	0.48	0.75	SXS

CROSSES

5035

5035-R



Cross


UNIV. FIG. NO.	NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES	DIM. B INCHES	JOINT
5035	3/4"	0.12	0.61	0.61	SXSXSXS
5035	1"	0.24	0.75	0.75	SXSXSXS
5035	1-1/4"	0.34	0.90	0.90	SXSXSXS
5035	1-1/2"	0.69	1.23	1.23	SXSXSXS
5035	2"	1.02	1.53	1.53	SXSXSXS
5035	2-1/2"	1.70	1.75	1.75	SXSXSXS
5035	3"		FUTURE OFFERING		
5035-R	1"x1"x3/4"x3/4"	0.18	0.61	0.73	SXSXSXS

BlazeMaster®

BlazeMaster® Fire Protection Fittings – STANDARD

ELBOWS


5006



45° Elbow

UNIV. FIG. NO.	NOM. SIZE	APPROX. NET WT./LBS.	DIM. J INCHES	JOINT
5006	3/4"	0.06	0.32	SXS
5006	1"	0.12	0.39	SXS
5006	1-1/4"	0.18	0.48	SXS
5006	1-1/2"	0.36	0.47	SXS
5006	2"	0.54	0.58	SXS
5006	2-1/2"	1.00	0.65	SXS
5006	3"	1.28	0.76	SXS

5007 5007-R



90° Elbow

UNIV. FIG. NO.	NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES	DIM. B INCHES	JOINT
5007	3/4"	0.08	0.56	0.56	SXS
5007	1"	0.14	0.69	0.69	SXS
5007	1-1/4"	0.22	0.91	0.91	SXS
5007	1-1/2"	0.41	1.06	1.06	SXS
5007	2"	0.60	1.24	1.24	SXS
5007	2-1/2"	1.16	1.50	1.50	SXS
5007	3"	1.66	1.81	1.81	SXS
5007-R	1"x3/4"	0.12	0.61	0.75	SXS


BlazeMaster®

BlazeMaster® Fire Protection Fittings – STANDARD

FLANGES

Future Offering


5019-H



Blind Flange – Solid

UNIV. FIG. NO.	NOM. SIZE	APPROX. NET WT./LBS.	DIM. G INCHES	DIM. OB INCHES
5019-H	3/4"	0.32	0.58	0.80
5019-H	1"	0.43	0.64	0.84
5019-H	1-1/4"	0.57	0.69	0.94
5019-H	1-1/2"	0.69	0.78	1.00
5019-H	2"	1.08	0.83	1.13
5019-H	2-1/2"	1.81	0.96	1.22
5019-H	3"	2.45	1.05	1.31


5051-A



Flange – Van Stone

UNIV. FIG. NO.	NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES	DIM. B INCHES	DIM. DO INCHES	DIM. RF INCHES	DIM. N INCHES	JOINT
5051-A	3"	1.75	2.41	0.99	7.50	4.81	0.50	S


5051-2-A



Flange – Van Stone

UNIV. FIG. NO.	NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES	DIM. B INCHES	DIM. DO INCHES	DIM. RF INCHES	DIM. N INCHES	JOINT
5051-2-A	3"	1.82	3.05	0.99	7.50	4.81	1.16	SPG

5051-H



Flange – Solid


UNIV. FIG. NO.	NOM. SIZE	APPROX. NET WT./LBS.	DIM. G INCHES	DIM. N INCHES	JOINT
5051-H	3/4"	0.31	0.58	0.17	S
5051-H	1"	0.41	0.64	0.18	S
5051-H	1-1/4"	0.53	0.69	0.20	S
5051-H	1-1/2"	0.68	0.78	0.23	S
5051-H	2"	1.03	0.83	0.27	S
5051-H	2-1/2"	1.61	1.96	0.20	S
5051-H	3"	2.08	1.05	0.29	S

BlazeMaster®

BlazeMaster® Fire Protection Fittings – STANDARD

TEES

5011
5011-R



Tees


UNIV. FIG. NO.	NOM. NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES	DIM. B INCHES	DIM. C INCHES	JOINT
5011	3/4"	0.10	0.57	0.57	0.57	SXSXS
5011	1"	0.17	0.69	0.69	0.69	SXSXS
5011	1-1/4"	0.28	0.89	0.89	0.89	SXSXS
5011	1-1/2"	0.58	1.05	1.05	1.05	SXSXS
5011	2"	0.82	1.25	1.25	1.25	SXSXS
5011	2-1/2"	1.58	1.53	1.53	1.53	SXSXS
5011	3"	2.14	1.84	1.84	1.84	SXSXS
5011-R	3/4"x3/4"x1"	0.14	0.70	0.70	0.73	SXSXS
5011-R	1"x1"x3/4"	0.16	0.61	0.61	0.94	SXSXS
5011-R	1"x3/4"x1"	0.20	0.76	0.99	0.78	SXSXS
5011-R	1"x3/4"x3/4"	0.16	0.60	0.87	0.77	SXSXS
5011-R	1-1/4"x1-1/4"x1"	0.24	0.73	0.73	0.89	SXSXS
5011-R	1-1/4"x1-1/4"x3/4"	0.20	0.60	0.60	0.89	SXSXS
5011-R	1-1/4"x1"x1-1/4"	0.28	0.88	1.03	0.87	SXSXS
5011-R	1-1/4"x1"x1"	0.24	0.71	0.90	0.89	SXSXS
5011-R	1-1/4"x1"x3/4"	0.20	0.61	0.76	0.89	SXSXS
5011-R	1-1/4"x1-1/4"x1-1/2"	0.44	1.01	1.01	0.88	SXSXS
5011-R	1-1/2"x1-1/2"x1-1/4"	0.46	0.89	0.89	1.04	SXSXS
5011-R	1-1/2"x1-1/2"x1"	0.54	0.77	0.77	0.96	SXSXS
5011-R	1-1/2"x1-1/2"x3/4"	0.50	0.67	0.67	1.04	SXSXS
5011-R	1-1/2"x1-1/4"x1"	0.40	0.72	0.91	1.01	SXSXS
5011-R	1-1/2"x1-1/4"x3/4"	0.36	0.60	0.78	1.02	SXSXS
5011-R	1-1/2"x1-1/2"x2"	0.88	1.30	1.30	1.14	SXSXS
5011-R	2"x2"x1-1/2"	0.86	1.06	1.06	1.37	SXSXS
5011-R	2"x2"x1-1/4"	0.67	1.00	1.00	1.28	SXSXS
5011-R	2"x2"x1"	0.72	0.80	0.80	1.25	SXSXS
5011-R	2"x2"x3/4"	0.68	0.70	0.70	1.25	SXSXS
5011-R	2-1/2"x2-1/2"x2"	1.83	1.53	1.53	1.93	SXSXS
5011-R	2-1/2"x2-1/2"x1-1/2"	1.94	1.53	1.53	2.08	SXSXS
5011-R	2-1/2"x2-1/2"x1-1/4"	1.95	1.53	1.53	2.47	SXSXS
5011-R	2-1/2"x2-1/2"x1"	1.94	1.53	1.53	2.59	SXSXS
5011-R	3"x3"x2-1/2"	2.61	1.84	1.84	2.45	SXSXS
5011-R	3"x3"x2"	1.86	1.36	1.36	1.82	SXSXS
5011-R	3"x3"x1-1/2"	2.87	1.84	1.84	2.55	SXSXS

BlazeMaster®

BlazeMaster® Fire Protection Fittings – STANDARD

UNIONS

5033-E



Unions (O-ring Material EPDM)

UNIV. FIG. NO.	NOM. NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES	DIM. L INCHES	JOINT
5033-E	3/4"	0.27	2.46	0.43	SXS
5033-E	1"	0.40	2.70	0.43	SXS
5033-E*	1-1/4"	0.87	3.31	0.79	SXS
5033-E*	1-1/2"	0.93	3.58	0.80	SXS
5033-E*	2"	1.83	3.82	0.80	SXS

* Future Offering

BlazeMaster®

CPVC Threaded Fire Protection Fittings


Adapters	15-16
Crosses	17
Elbows	17
Tees	18
Test Plugs	19
Union End Connectors	19

BlazeMaster®

BlazeMaster® Fire Protection Fittings – THREADED

ADAPTERS


5003-BI



Female Adapter with Metal Thread Inserts

UNIV. FIG. NO.	NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES	JOINT
5003-BI	3/4"	0.28	1.19	SXFNPT
5003-BI	1"	0.63	1.59	SXFNPT
5003-BI	1-1/4"	1.02	1.96	SXFNPT
5003-BI	1-1/2"	1.26	1.98	SXFNPT
5003-BI	2"	1.98	1.99	SXFNPT


5003-2-BI



Spigot Female Adapter with Metal Thread Inserts

UNIV. FIG. NO.	NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES	JOINT
5003-2-BI	3/4"	0.28	2.00	SPGXFNPT
5003-2-BI	1"	0.61	2.72	SPGXFNPT

5003-S-BI



Female Sprinkler Head Adapter with Metal Thread Inserts


UNIV. FIG. NO.	NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES	JOINT
5003-S-BI	3/4"x1/2"	0.16	0.72	SXFNPT
5003-S-BI	1"x1/2"	0.18	0.73	SXFNPT
5003-S-BI	1"x3/4"	0.18	0.93	SXFNPT

BlazeMaster®

BlazeMaster® Fire Protection Fittings – THREADED

ADAPTERS


5003-2-S-BI



Spigot Female Sprinkler Head Adapter with Metal Thread Inserts

UNIV. FIG. NO.	NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES	JOINT
5003-2-S-BI	1"x1/2"	0.16	1.84	SPGXFNPT
5003-2-S-BI	3/4"x1/2"	0.15	1.53	SPGXFNPT

5004-BI



Male Adapter with Metal Thread Inserts

UNIV. FIG. NO.	NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES	JOINT
5004-BI	3/4"	0.22	1.35	SxMNPT
5004-BI	1"	0.46	1.82	SxMNPT
5004-BI	1-1/4"	0.74	2.05	SxMNPT
5004-BI	1-1/2"	1.06	2.14	SxMNPT
5004-BI	2"	1.80	2.31	SxMNPT


BlazeMaster®

BlazeMaster® Fire Protection Fittings – THREADED

CROSSES

5035-3-S-BI-S

5035-3-S-BI-L




Sprinkler Head Back To Back Cross with Metal Thread Inserts

UNIV. FIG. NO.	NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES	DIM. B INCHES	DIM. C INCHES	DIM. D INCHES	JOINT
5035-3-S-BI-S	1x1"x1/2"x1/2" 3-3/8" Take Out	0.46	1.69	1.69	0.62	0.62	SXSXFNPTXFNPT
5035-3-S-BI-L	1x1"x1/2"x1/2" 3-5/8" Take Out	0.48	1.81	1.81	0.62	0.62	SXSXFNPTXFNPT

ELBOWS

5007-3-S-BI



Sprinkler Head 90 with Metal Thread Inserts


UNIV. FIG. NO.	NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES	DIM. B INCHES	JOINT
5007-3-S-BI	3/4"x1/2"	0.22	0.56	1.62	SxFNPT
5007-3-S-BI	1"x1/2"	0.27	0.50	1.76	SxFNPT
5007-3-S-BI	1"x3/4"	0.26	0.59	1.88	SxFNPT
5007-3-S-BI	1-1/4"x1/2"	0.30	0.48	1.95	SxFNPT

BlazeMaster®

BlazeMaster® Fire Protection Fittings – THREADED

TEES


5011-3-3-S-BI-S
5011-3-3-S-BI-L



Back To Back Tee with Metal Thread Inserts

UNIV. FIG. NO.	NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES	DIM. B INCHES	DIM. C INCHES	JOINT
5011-3-3-S-BI-S	1/2"x1/2"x1" 3-3/8" Take Out	0.44	1.69	1.69	.62	FNPTXFNPTXS
5011-3-3-S-BI-L	1/2"x1/2"x1" 3-5/8" Take Out	0.48	1.81	1.81	.62	FNPTXFNPTXS


5012-S-BI
5012R-S-BI



Sprinkler Head Tee with Metal Thread Inserts

UNIV. FIG. NO.	NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES	DIM. B INCHES	DIM. C INCHES	JOINT
5012-S-BI	3/4"x3/4"x1/2"	0.22	0.42	0.42	1.60	SXSXFNPT
5012-S-BI	1"	0.44	0.80	0.80	1.48	SXSXFNPT
5012-S-BI	1"x1"x1/2"	0.29	0.41	0.41	1.76	SXSXFNPT
5012-S-BI	1-1/4"x1-1/4"x1/2"	0.34	0.52	0.52	1.95	SXSXFNPT
5012-S-BI	1-1/2"x1-1/2"x1/2"	0.46	0.45	0.45	2.13	SXSXFNPT
5012-S-BI	2"x2"x1/2"	0.58	0.47	0.47	1.68	SXSXFNPT
5012R-S-BI	1"x3/4"x1/2"	0.28	0.46	0.83	1.69	SXSXFNPT
5012R-S-BI	1-1/4"x1"x1/2"	0.34	0.51	0.63	1.94	SXSXFNPT
5012R-S-BI	1-1/2"x1-1/4"x1/2"	0.47	0.46	0.67	2.13	SXSXFNPT
5012R-S-BI	2"x1-1/2"x1/2"	0.58	0.48	0.78	2.38	SXSXFNPT

5014R-S-BI



Sprinkler Head Tee with Metal Thread Inserts



UNIV. FIG. NO.	NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES	DIM. B INCHES	DIM. C INCHES	JOINT
5014R-S-BI	1"x1/2"x1"	0.30	0.71	1.74	1.90	SXFNPTXS

BlazeMaster®

BlazeMaster® Fire Protection Fittings – THREADED

TEST PLUG

450-005



Test Plug

UNIV. FIG. NO.	NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES	JOINT
450-005	1/2"	0.03	1.06	MPT

Note: Test plug is white PVC Schedule 40 material and is intended for testing the system only. Test plug should not be included as a component in the completed system.

UNION END CONNECTORS

TCBR-3



Brass End Connector

UNIV. FIG. NO.	NOM. SIZE	APPROX. NET WT./LBS.	DIM. A INCHES	DIM. T INCHES	JOINT
TCBR-3	1/2"	0.33	1.02	0.43	FNPT
TCBR-3	3/4"	0.43	1.02	0.45	FNPT
TCBR-3	1"	0.52	1.19	0.53	FNPT
TCBR-3	1-1/4"	0.85	1.42	0.55	FNPT
TCBR-3	1-1/2"	1.81	1.42	0.55	FNPT
TCBR-3	2"	2.74	1.57	0.57	FNPT
TCBR-3	3"	5.45	2.25	0.95	FNPT

BlazeMaster®

BlazeMaster® Fire Protection Fittings – ACCESSORIES

CEMENT AND ACCESSORIES



Solvent Cement

FIG. NO.	SIZE	DESCRIPTION	LBS./CASE
5097Q	Quart	NIBCO FP-1000 One Step Cement	27
5097P	Pint	NIBCO FP-1000 One Step Cement	14
C5097Q	Quart	NIBCO FP-1000 One Step Cement Canada compliant label	27
C5097P	Pint	NIBCO FP-1000 One Step Cement Canada compliant label	14



Empty Can

FIG. NO.	SIZE	DESCRIPTION	LBS./CASE
5098Q	Quart	Empty Can Quart	3
5098P	Pint	Empty Can Pint	2
5098G	Gallon	Empty Can Gallon	5

Note: Pint can lid is the correct size dauber for 3/4" through 1-1/4" pipe and fitting assembly; quart can lid is the correct size dauber for 1-1/2" through 3" pipe and fittings.



Brush

FIG. NO.	SIZE	DESCRIPTION	LBS./CASE
5096	NA	Brush BP-1	11



Roller

FIG. NO.	SIZE	DESCRIPTION	LBS./CASE
5097	NA	Roller 6020	4



Dauber

FIG. NO.	SIZE	DESCRIPTION	LBS./CASE
5093S	Small	Dauber CM-75 (for pipe sizes 3/4" - 1-1/4")	2
5093L	Large	Dauber CM-150 (for pipe sizes 1-1/4" - 3")	2

BlazeMaster®

BlazeMaster® Fire Protection Fittings – ACCESSORIES

CEMENT AND ACCESSORIES



Thread Sealant

FIG. NO.	SIZE	DESCRIPTION	LBS./CASE
5094	Pint	Thread Sealant	22

**Only use thread sealant that is compatible with NIBCO manufactured BlazeMaster® CPVC fittings. Thread sealants which carry FGG/BM® System Compatible mark have been determined to be chemically compatible.*




PTFE Tape

FIG. NO.	SIZE	DESCRIPTION	LBS./CASE
5099	1/2"x260"	PTFE Tape	11

BlazeMaster®

Typical Residential Riser

NIBCO valves and fittings that are typically used with CPVC fire protection pipe.







- 1 CPVC Fire Protection Pipe
- 2 NIBCO #5012-S-BI
- 3 Pressure Gauge
- 4 NIBCO #5011
- 5 NIBCO #5004-BI
- 6 NIBCO Hose End
T-585-70-HC / 66-HC
- 7 Flow Switch
- 8 NIBCO Check
T-480, T-480-Y, T-413-Y, TI3
- 9 NIBCO Isolation
T-585-70 / 66 / UL / IC
MTT-585-70, T-FP-600,
S50-B-C-E

BlazeMaster®

Valves for Residential Fire Protection


ISOLATION VALVES

<p>T-585-70 / 66</p>  <p>600 PSI CWP 150 PSI SWP 2-Piece Bronze Body Full Port Bronze or SS Stem Chrome/Nickel Plate or SS Ball Threaded Connection MSS SP-110 1/4" – 2"</p>	<p>KT-580-70-UL KT-585-70-UL</p>  <p>300 PSI Non-Shock Cold Water 2-Piece Bronze Body Full Port 1/4" – 1", Conventional Port 1-1/4" – 3" Bronze Stem Chrome/Nickel Plate Ball Threaded Connection MSS SP-110, UL/FM 1/4" – 3"</p>	<p>MTT-585-70</p>  <p>600 PSI CWP 150 PSI SWP 2-Piece Bronze Body Full Port Bronze Stem, Chrome Chrome/Nickel Plate Ball Male x Female Threaded End Connection MSS SP-110 1/2" – 2"</p>
<p>T-FP-600A</p>  <p>600 PSI CWP 2-Piece Brass Body Full Port Bronze or Brass Stem Chrome/Nickel Plate Ball Threaded Connection MSS SP-110, UL 1/4" – 2"</p>		

CHECK VALVES

<p>T-413-Y/W</p>  <p>200 PSI CWP Horizontal Swing Check Bronze Body PTFE or Buna Disc Integral Seat Threaded Connection MSS SP-80 1/2" – 2"</p>	<p>T-480-Y T-480</p>  <p>250 PSI CWP In-Line Lift Type Check Bronze Body PTFE or Buna Disc Integral Seat Threaded Connection 3/8" – 2"</p>
---	--


HOSE END DRAIN

<p>T-585-70-HC / 66-HC</p>  <p>600 PSI CWP Ball Valve with Cap & Chain 2-Piece Bronze Body Full Port Bronze or SS Stem Chrome Plated or SS Ball Threaded Connection MSS SP-110 1/2" – 3/4"</p>
--


NOTE: To view NIBCO's entire fire protection valve offering, visit www.nibco.com.

BlazeMaster®


Hangers for Residential Fire Protection




TOLCO Fig. 22 –Hanger for CPVC Plastic Pipe Single Fastener Strap Type




TOLCO Fig. 23 –Hanger for CPVC Plastic Pipe Double Fastener Strap Type




TOLCO Fig. 24 –Hanger for CPVC Plastic Pipe Double Fastener Strap Type – Side Mount



TOLCO Fig. 29 – Double Offset Hanger & Restrainer for CPVC Plastic Pipe



TOLCO Fig. 28 –"Stand-Off" Hanger & Restrainer for CPVC Plastic Pipe



TOLCO Fig. 28M – CPVC Hanger and Restrainer for CPVC Plastic Pipe

Note: To view TOLCO's entire fire protection hanger & strut offering, visit www.nibco.com.

Review – Do's & Don'ts

Do's

- Installation should be made only by a qualified installer or contractor in accordance with all applicable codes and requirements.
- Read and follow the installation instructions.
- Follow recommended safe work practices.
- Make certain that thread sealants, gasket lubricants, or firestop materials are compatible with CPVC.
- Keep pipe and fittings in original packaging until needed.
- Cover pipe and fittings with an opaque tarp if stored outdoors.
- Follow proper handling procedures.
- Use tools specifically designed for use with plastic pipe and fittings.
- Use the proper solvent cement and follow application instructions.
- Use a drop cloth to protect interior finishes.
- Cut the pipe ends square.
- Deburr and bevel the pipe end with a chamfering tool.
- Rotate the pipe 1/4 turn when bottoming pipe in fitting socket.
- Make certain no solvent cement is on sprinkler head and adapter threads.
- Make certain that solvent cement does not run and plug the sprinkler head orifice.
- Follow the manufacturer's recommended cure times prior to pressure testing.
- Fill lines slowly and only at a proper pressure.
- Bleed the air from the system prior to pressure testing.
- Support sprinkler head properly to prevent lift up of the head through the ceiling when activated.
- Keep threaded rod within 1/16" of the pipe or use a surge arrestor.
- Install NIBCO® **BlazeMaster**® CPVC Fire Sprinkler Products in wet systems only.
- Use only insulation and/or glycerin and water solutions for freeze protection.
- Allow for movement due to expansion and contraction.
- Ensure installers have been properly trained per the NIBCO **BlazeMaster**® CPVC Fire Sprinkler System Installation and Design Manual and renew your training every three years at a minimum.

Don'ts

- Do not use edible oils such as Crisco® as a gasket lubricant.
- Do not use petroleum or solvent-based sealants, lubricants, or fire stop materials.
- Do not use any glycol-based solutions as an anti-freeze.
- Do not contaminate the CPVC system with cutting oils or compressor oils.
- Do not mix glycerin and water solutions in contaminated containers.
- Do not use solvent cement that exceeds its shelf life or has become discolored or jellied.
- Do not allow solvent cement to plug the sprinkler head orifice.
- Do not connect rigid metal couplers to CPVC grooved adapters.
- Do not thread or groove CPVC pipe.
- Do not use solvent cement near sources of heat, open flame, or when smoking.
- Do not pressure test with air.
- Do not pressure test until recommended cure times are met.
- Do not exceed proper pressure for testing.
- Do not use ratchet cutters below 50°F.
- Do not use CPVC pipe that has been stored outdoors, unprotected and is faded in color.
- Do not allow threaded rod to come in contact with the pipe.
- Do not install NIBCO **BlazeMaster**® CPVC Fire Sprinkler Products in cold weather without allowing for expansion.
- Do not install NIBCO **BlazeMaster**® CPVC Fire Sprinkler Products in dry systems.
- Do not allow puddling of cement in fittings and pipe.
- Do not use dull or broken cutting tool blades when cutting pipe.

BlazeMaster®

CPVC Cross Reference Sheet

STANDARD FITTINGS

	NIBCO FIG. NO.	SIZE	SPEARS FIG. NO.	TYCO FIG. NO.	
ADAPTER	5001-G	1-1/4"	4233-012	80160	
	5001-G	1-1/2"	4233-015	80161	
	5001-G	2"	4233-020	80162	
	5001-G	2-1/2"	4233-025	80163	
	5001-G	3"	4233-030	80164	
BUSHINGS	5018	1"x3/4"	4237-131	80200	
	5018	1-1/4"x1"	4237-168	80202	
	5018	1-1/4"x3/4"	4237-167	80201	
	5018	1-1/2"x1-1/4"	4237-212	80205	
	5018	1-1/2"x1"	4237-211	80204	
	5018	1-1/2"x3/4"	4237-210	80203	
	5018	2"x1-1/2"	4237-251	80209	
	5018	2"x1-1/4"	4237-250	80208	
	5018	2"x1"	4237-249	80207	
	5018	2"x3/4"	4237-248	80206	
	5018	2-1/2"x2"	4237-292	80211	
	5018	2-1/2"x1-1/2"	4237-291	80213	
	5018	2-1/2"x1-1/4"	4237-290	80214	
	5018	2-1/2"x1"	N/A	80215	
	5018	3"x2-1/2"	4237-339	80212	
	5018	3"x2"	4237-338	80210	
	CAPS	5017	3/4"	4247-007	80100
		5017	1"	4247-010	80101
		5017	1-1/4"	4247-012	80102
		5017	1-1/2"	4247-015	80103
5017		2"	4247-020	80104	
5017		2-1/2"	4247-025	80105	
5017		3"	4247-030	80106	
COUPLINGS	5001	3/4"	4229-007	80075	
	5001	1"	4229-010	80076	
	5001	1-1/4"	4229-012	80077	
	5001	1-1/2"	4229-015	80078	
	5001	2"	4229-020	80079	
	5001	2-1/2"	4229-025	80080	
	5001	3"	4229-030	80081	
	5001-R	1"x3/4"	4229-131	80220	
	5001-R	1-1/4"x1"	4229-168	N/A	
	5001-R	1-1/2"x3/4"	4229-210	N/A	
CROSSES	5035	3/4"	4220-007	80009	
	5035	1"	4220-010	80010	
	5035	1-1/4"	4220-012	80011	

STANDARD FITTINGS

	NIBCO FIG. NO.	SIZE	SPEARS FIG. NO.	TYCO FIG. NO.
CROSSES	5035	1-1/2"	4220-015	80012
	5035	2"	4220-020	80013
	5035	2-1/2"	4220-025	80014
	5035	3"	4220-030	80008
	5035-R	1"x3/4"x1"x3/4"	4220-131	80015
	5006	3/4"	4217-007	80050
	5006	1"	4217-010	80051
	5006	1-1/4"	4217-012	80052
	5006	1-1/2"	4217-015	80053
	5006	2"	4217-020	80054
ELBOWS	5006	2-1/2"	4217-025	80055
	5006	3"	4217-030	80056
	5007	3/4"	4206-007	80025
	5007	1"	4206-010	80026
	5007	1-1/4"	4206-012	80027
	5007	1-1/2"	4206-015	80028
	5007	2"	4206-020	80039
	5007	2-1/2"	4206-025	80030
	5007	3"	4206-030	80031
	5007-R	1"x3/4"	4206-131	80032
FLANGES	5019-H	3/4"	4253-007	N/A
	5019-H	1"	4253-010	N/A
	5019-H	1-1/4"	4253-012	N/A
	5019-H	1-1/2"	4253-015	N/A
	5019-H	2"	4253-020	N/A
	5019-H	2-1/2"	4253-025	N/A
	5019-H	3"	4253-030	N/A
	5051-A	3"	4254-030	N/A
	5051-2-A	3"	4256-030	N/A
	5051-H	3/4"	4251-007	N/A
TEES	5051-H	1"	4251-010	N/A
	5051-H	1-1/4"	4251-012	N/A
	5051-H	1-1/2"	4251-015	N/A
	5051-H	2"	4251-020	N/A
	5051-H	2-1/2"	4251-025	N/A
	5051-H	3"	N/A	N/A
	5011	3/4"	4201-007	8000
	5011	1"	4201-010	8001
	5011	1-1/4"	4201-012	8002
	5011	1-1/2"	4201-015	8003
5011	2"	4201-020	80004	
5011	2-1/2"	4201-025	8005	
5011	3"	4201-030	80006	
5011-R	3/4"x3/4"x1"	4201-102	80132	
5011-R	1"x1"x3/4"	4201-131	80260	

BlazeMaster®

CPVC Cross Reference Sheet

STANDARD FITTINGS


	NIBCO FIG. NO.	SIZE	SPEARS FIG. NO.	TYCO FIG. NO.
TEES	5011-R	1"x3/4"x1"	4201-126	80134
	5011-R	1"x3/4"x3/4"	4201-125	80133
	5011-R	1-1/4"x1-1/4"x1"	4201-168	80262
	5011-R	1-1/4"x1-1/4"x3/4"	4201-167	80261
	5011-R	1-1/4"x1"x1-1/4"	4201-159	80137
	5011-R	1-1/4"x1"x1"	4201-158	80136
	5011-R	1-1/4"x1"x3/4"	4201-157	80135
	5011-R	1-1/4"x1-1/4"x1-1/2"	4201-169	80138
	5011-R	1-1/2"x1-1/2"x1-1/4"	4201-212	80275
	5011-R	1-1/2"x1-1/2"x1"	4201-211	80264
	5011-R	1-1/2"x1-1/2"x3/4"	4201-210	80263
	5011-R	1-1/2"x1-1/4"x1"	4201-202	80140
	5011-R	1-1/2"x1-1/4"x3/4"	4201-201	80140
	5011-R	1-1/2"x1-1/2"x2"	4201-213	N/A
	5011-R	2"x2"x1-1/2"	4201-251	80274
	5011-R	2"x2"x1-1/4"	4201-250	80267
	5011-R	2"x2"x1"	4201-249	80266
	5011-R	2"x2"x3/4"	4201-248	80265
	5011-R	2-1/2"x2-1/2"x2"	4201-292	80276
	5011-R	2-1/2"x2-1/2"x1-1/2"	4201-291	80273
	5011-R	2-1/2"x2-1/2"x1-1/4"	4201-290	80272
	5011-R	2-1/2"x2-1/2"x1"	4201-289	80271
	5011-R	3"x3"x2-1/2"	4201-339	80269
	5011-R	3"x3"x2"	4201-338	80268
	5011-R	3"x3"x1-1/2"	4201-337	80270
UNIONS	5033-E	3/4"	4257-007	N/A
	5033-E	1"	4257-010	N/A
	5033-E	1-1/4"	4257-012	N/A
	5033-E	1-1/2"	4257-015	N/A
	5033-E	2"	4257-020	N/A
	5033-E	2-1/2"	N/A	N/A
	5033-E	3"	N/A	N/A

THREADED FITTINGS

	NIBCO FIG. NO.	SIZE	SPEARS FIG. NO.	TYCO FIG. NO.
ADAPTERS	5003-BI	3/4"	4235-007	80142
	5003-BI	1"	4235-010	80145
	5003-BI	1-1/4"	4235-012	80146
	5003-BI	1-1/2"	4235-015	80147
	5003-BI	2"	4235-020	80148
	5003-2-BI	3/4"	4278-007	N/A
	5003-2-BI	1"	4278-010	N/A
	5003-S-BI	3/4"x1/2"	4235-101	80175E or 80175W
	5003-S-BI	1"x1/2"	4235-130	80176E or 80175W
	5003-S-BI	1"x3/4"	4235-131	80179
	5003-2-S-BI	3/4"x1/2"	4238-101	N/A
	5003-2-S-BI	1"x1/2"	4238-130	N/A
	5004-BI	3/4"	N/A	80157
	5004-BI	1"	N/A	80158
	5004-BI	1-1/4"	N/A	N/A
5004-BI	1-1/2"	N/A	N/A	
5004-BI	2"	N/A	N/A	
CROSSES	5035-3-S-BI-S	1"x1"x1/2"x1/2"	N/A	80462
	5035-3-S-BI-L	1"x1"x1/2"x1/2"	N/A	80463
ELBOWS	5007-3-S-BI	3/4"x1/2"	4207-101	80199
	5007-3-S-BI	1"x1/2"	4207-130	80198
	5007-3-S-BI	1"x3/4"	4207-131	N/A
	5007-3-S-BI	1-1/4"x1/2"	4207-166	N/A
	5011-3-3-S-BI-S	1/2"x1/2"x1"	N/A	80460
5011-3-3-S-BI-L	1/2"x1/2"x1"	N/A	80459	
TEES	5012-S-BI	1"	4202-010	N/A
	5012-S-BI	3/4"x3/4"x1/2"	4202-101	80250
	5012-R-S-BI	1"x3/4"x1/2"	4202-124	N/A
	5012-S-BI	1"x1"x1/2"	4202-130	80251
	5012-R-S-BI	1"x1/2"x1"	4203-122	N/A
	5012-R-S-BI	1-1/4"x1"x1/2"	4202-156	80256
	5012-S-BI	1-1/4"x1-1/4"x1/2"	4202-166	80252
	5012-R-S-BI	1-1/2"x1-1/4"x1/2"	4202-199	80257
	5012-S-BI	1-1/2"x1-1/2"x1/2"	4202-209	80254
	5012-S-BI	2"x2"x1/2"	4202-247	80253
5012-R-S-BI	2"x1-1/2"x1/2"	4202-237	80258	
TEST PLUG	450-005	1/2"	4250-005	N/A
UNION CONNECTOR	TCBR-3	3/4"	N/A	N/A
	TCBR-3	1"	N/A	N/A
	TCBR-3	1-1/4"	N/A	N/A
	TCBR-3	1-1/2"	N/A	N/A
	TCBR-3	2"	N/A	N/A
	TCBR-3	3"	N/A	N/A

BlazeMaster®

NIBCO® Fire Protection Solutions



NIBCO represents a tradition of quality, service, highly specified valves and TOLCO support systems for the fire protection market. We offer a winning combination of fire protection solutions that meet industry standards including UL, ULC, FMRC and NYC.

TOLBrace®
VERSION 6.0 Fire SP5.0
 Seismic Bracing Calculation Program
 Per NFPA 13, 1999 and 2002 Edition
 (includes TIA 02-1)

- Imperial or Metric Units
- Calculations Prepared and Printable

LEADERS in
Seismic Bracing
Technology

NOTES

NIBCO LIMITED WARRANTY

Applicable to NIBCO INC. CPVC FIRE PROTECTION Plastic Fittings

NIBCO INC. warrants each NIBCO **BlazeMaster**® Fire Protection CPVC plastic fitting to be free from defects in materials and workmanship under normal use and service for a period of ten (10) years from the date of purchase.

In the event any defect occurs which the owner believes is covered by this Warranty, the owner should immediately contact NIBCO INC., Technical Services, either in writing or by telephone call, (888) 446-4226 or (574) 295-3000. The owner will be instructed to return said fitting or valve, at the owner's expense, to NIBCO INC. or an authorized NIBCO INC. representative for inspection. In the event said inspection discloses to NIBCO INC.'s satisfaction that said fitting or valve is defective, a replacement shall be mailed free of charge to the owner, and NIBCO INC. shall further pay the installing contractor the sum of ten (\$10.00) dollars to apply on the cost of installation of said replacement fitting.

TO THE EXTENT PERMITTED BY LAW, THIS WARRANTY SPECIFICALLY EXCLUDES INCIDENTAL AND CONSEQUENTIAL DAMAGES OF EVERY TYPE AND DESCRIPTION RESULTING FROM ANY CLAIMED DEFECT IN MATERIAL OR WORKMANSHIP, INCLUDING BUT NOT LIMITED TO, PERSONAL INJURIES AND PROPERTY DAMAGES. Some states do not allow the exclusion or limitations of incidental or consequential damages, so these limitations may not apply to you. **TO THE EXTENT PERMITTED BY LAW, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE LIMITED IN DURATION.**

This Warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

NIBCO® NIBCO INC. World Headquarters • 1516 Middlebury St. • Elkhart, IN 46516-4740 USA • www.nibco.com

how to order

NIBCO sells its products through select stocking distributors. Our distributors are knowledgeable about plastics fittings as well as the complete line of NIBCO Fire Protection Systems.


Please visit www.nibco.com for a complete listing of authorized NIBCO distributors in your area.

NIBCO INC. Customer Service
World Headquarters
1516 Middlebury Street
P.O. Box 1167
Elkhart, IN 46515-1167
USA
Phone: 800.234.0227
Fax: 800.234.0557

To the best of our knowledge the information contained in this publication is accurate. However, NIBCO® does not assume any liability whatsoever for the accuracy or completeness of such information. Final determinations of the suitability of any information or product for the use to be contemplated is the sole responsibility of the user. The manner of that use, and whether there is any infringement of patents, is also the sole responsibility of the user.

BlazeMaster® is a registered trademark of The Lubrizol Corporation

globally connecting you at all levels



It's a new age of business, and a new way at NIBCO. From Elkhart, Indiana to Lodz, Poland, and points beyond, our company has integrated manufacturing, distribution, and networked communications to provide a seamless source of information and service, 24 hours a day, 7 days a week. But this integration hasn't happened overnight. It's been part of a long-term strategic process that has pushed us to reconsider every aspect of our business. The result? We're a vertically integrated manufacturer with the products and systems in place to deliver low cost and high quality. NIBCO's products are manufactured under a Quality Management System conforming to the current revision of ISO-9001 International Standards. We know the flow control industry is only going to get more demanding, and we are more than ready. We will continue to lead. That's what NIBCO is all about.




FEATURING NIBCO® SYSTEMS

C-BLZM-1009

NIBCO® DURA-PEX® Piping Systems • NIBCO® Press System®

FITTINGS




Wrot and cast copper pressure and drainage fittings • Cast copper alloy flanges
• Wrot and cast press fittings • ABS and PVC DWV fittings • Schedule 40 PVC
pressure fittings • CPVC CTS fittings • CPVC CTS-to-metal transition fittings •
Schedule 80 PVC and CPVC systems • CPVC metric piping systems • CPVC
BlazeMaster® fire protection fittings

BlazeMaster® is a registered trademark of The Lubrizol Corporation.

VALVES & ACTUATION

Pressure-rated bronze, iron and alloy-iron gate, globe and check valves • Pressure-
rated bronze ball valves • Boiler specialty valves • Commercial and industrial
butterfly valves • Circuit balancing valves • Carbon and stainless steel ball valves
• ANSI flanged steel ball valves • Pneumatic and electric actuators and controls
• Grooved ball and butterfly valves • High performance butterfly valves • UL/FM
fire protection valves • MSS specification valves • Bronze specialty valves • Low
pressure gate, globe, check and ball valves • Frostproof sillcocks • Quarter-turn
supply stops • Quarter-turn low pressure valves • PVC ball valves • CPVC CTS ball
valves • Just Right® recirculating valves



CHEMTROL®



Thermoplastic pipe, valves and fittings in PVC, Corzan® CPVC, polypropylene
and PVDF Kynar® • Pneumatic and electric actuation systems

Corzan® is a registered trademark of The Lubrizol Corporation. • Kynar® is a registered trademark of Arkema Inc.

TOLCO®

Pipe attachments • Structural attachments • Pipe rollers • Threaded products
and accessories • Seismic components • Standard and specialty supports
• Markets served include commercial, industrial & fire protection



eNIBCO



EDI—Electronic Data Interchange • VMI—Vendor Managed Inventory •
NIBCO.com • NIBCOpartner.com

NIBCO®

AHEAD OF THE FLOW®

NIBCO INC.
WORLD HEADQUARTERS
WEB: www.nibco.com

1516 MIDDLEBURY STREET
ELKHART, IN 46516-4740
USA

DOMESTIC CUSTOMER SERVICE
PHONE: 800.234.0227
FAX: 800.234.0557

TECHNICAL SERVICE
PHONE: 888.446.4226
FAX: 888.336.4226

INTERNATIONAL OFFICE
PHONE: +1/574.295.3327
FAX: +1/574.295.3455